

ニューエクセルラインシリーズコンベヤベルト標準サイズ仕様一覧表

タイプ	用途	名称	呼称	仕様					ベルト幅 (mm)												参考値					
				ゴム質 表面形状	帆布 材質	ベルト強力 (N/mm)	プライ数	カバーゴム厚 上ゴム×下ゴム (mm)	300	350	400	450	500	600	700	750	800	900	1050	1200	1400	総厚 (約mm)	重量 (約kg/m ²)	最大1巻長さ (約m)		
普	耐摩耗用	ニューエクセル	NX 100/1	耐摩耗	TF	100	1	1.5×1.5	●	●	●	●	●	●								4.3	5.6	250		
			NX 125/2		TF	125	2	3.0×1.5	●	●	●	●	●										6.1	7.9	125・250	
			NX 160/2		TF	160	2	3.0×1.5			●	●	●	●	●	●								6.2	8.0	250
			NX 250/2		TF	250	2	5.0×1.5			●	●	●	●	●	●	●							8.1	10.3	125・250
			NX 315/3		TF	315	3	5.0×1.5					●	●	●	●	●	●						8.7	11.2	250
			NX 400/3		TF	400	3	5.0×1.5						●	●	●	●	●						9.0	11.6	250
			NX 500/3		TF	500	3	5.0×1.5						●	●	●	●	●	●					9.6	12.5	250
			NXH 315/3		TF	315	3	6.5×2.5					●	●		●		●						11.4	13.8	250・300
			NXH 400/3		TF	400	3	6.5×2.5								●		●	●					11.5	13.9	300
			NXH 500/3		TF	500	3	6.5×2.5								●	●	●	●	●	●			12.3	15.2	300
			NXH 630/4		TF	630	4	6.5×2.5								●		●	●					13.4	16.5	300
			NXH 630/4		TF	630	4	8.0×3.0													●	●		15.2	18.7	300
			NXH 800/4		TF	800	4	8.0×3.0												●	●	●	●	15.3	18.8	300
通	耐衝撃 耐カット用	ロックエクセル ハイパー	RX 315/2	耐摩耗 耐カット	TF	315	2	6.0×3.0					●	●	●	●	●				11.4	13.8	250			
			RX 400/2		TF	400	2	6.0×3.0					●	●	●	●	●					12.0	14.3	250		
			RX 500/2		TF	500	2	6.0×3.0						●	●	●	●	●	●				12.1	14.4	250	
			RX 630/2		TF	630	2	8.0×3.0										●	●	●	●		14.8	18.1	250	
			RX 800/3		TF	800	3	10.0×3.0											●	●	●	●	18.9	23.0	250	
			RX 1000/3		TF	1000	3	10.0×3.0												●	●	●	19.0	23.1	250	
超耐摩耗用	超耐摩耗 附着防止用	ファインエクセル	FX 250/2	超耐摩耗 附着防止用	TF	250	2	5.0×1.5				●	●	●	●						8.1	9.8	125・250			
			FX 315/3		TF	315	3	5.0×1.5				●	●		●						8.7	10.7	250			
			FXH 315/3		TF	315	3	6.5×2.5					●		●							11.5	13.7	300		
			FXH 500/3		TF	500	3	6.5×2.5						●		●	●	●				12.1	14.6	300		
特	傾斜用	クライムエクセル	CX 100/1	中寄棧付	TF	100	1	1.5×1.5	●	●	●										5.1	7.9	140			
			CX 125/2		TF	125	2	3.0×1.5			●	●	●	●							7.0	10.5	140			
			CX 160/2		TF	160	2	3.0×1.5					●	●							7.1	10.6	140			
		ラフトップAエクセル	RA 160/2	網目	TF	160	2	2.5×1.0	●	●	●	●	●	●		●			●		5.7	7.9	100			
		ラフトップBエクセル	RB 160/2	M型	TF	160	2	1.5×1.0	●	●	●	●	●		●			●			4.2	8.4	100			
殊	耐熱用	ヒートエクセル	HX 160/2	中温耐熱 (F-110)	NF	160	2	3.0×1.5			●	●									5.7	7.0	200			
			HX 250/3		NF	250	3	5.0×1.5				●	●	●	●						8.4	10.3	200			
	耐油用	オイルエクセル	OX 160/2	重耐油 (オイルエースH)	TF	160	2	3.0×1.5			●	●									5.8	7.1	200			
			OX 250/3		TF	250	3	3.0×1.5					●	●							6.6	8.1	200			

■用途は
①呼称②ベルト幅③長さ
または①名称②ベルト強力③ベルト幅④長さでお願いいたします。

100kgf/cm=98.1N/mmです

■帆布材質：TFはポリエステル帆布。NFはナイロン帆布。
■総厚：CX、RBは表面凹凸ふくまず。RAは溝の中心まで。
■最大1巻長さ：NX125/300幅・NX250/400幅・FX250/400幅は125M。NXH315/500幅は250M。
■これ以外のサイズ、仕様についてはオーダーメイドベルトで製造いたします。ご相談下さい。